

## Using site-specific nitrogen management in rainfed corn to reduce the risk of nitrate leaching

Maria del Pilar Muschietti-Piana <sup>a,b</sup>, Pablo Ariel Cipriotti <sup>c</sup>, Susana Urricariet <sup>b</sup>, Nahuel Raul Peralta <sup>d</sup>, Mauricio Niborski <sup>b</sup>

<sup>a</sup> Department of Natural Resources and Environment, School of Agriculture, Universidad de Buenos Aires, C1417DSE BA, Argentina

<sup>b</sup> Department of Land Use and Agriculture, School of Agriculture, Universidad de Buenos Aires, C1417DSE BA, Argentina

<sup>c</sup> Department of Quantitative Methods and Information Systems, School of Agriculture – IFEVA, Universidad de Buenos Aires/CONICET, C1417DSE BA, Argentina

<sup>d</sup> Department of Market and Development of Corn, BAYER Crop Science. Ruta 8, Fontezuela, Pergamino, Argentina

**Keywords:** Management zones, Yield potential, Soil residual-nitrogen, Water use efficiency, Drought, Nitrogen use efficiency

**Abstract:** Managing nitrogen (N) to achieve yield potential and limit losses to the environment is challenging due to the temporal and spatial variability in crop N uptake which affects the distribution of soil-N. Nitrogen fertilization using site-specific management (SSM) is one of a number of strategies that can improve the efficiency of N use and reduce the losses of N to the environment from cropping systems. The aim was to assess: (i) corn (*Zea mays* L.) grain yield and N uptake; and (ii) soil residual- and potentially leachable-N, and its relationship with N and water use efficiency using SSM vs. uniform management (UM) strategies in high-(HP) and low-(LP) productivity zones on soils of the Inland Pampas of Argentina. Differences in soil residual- and potentially leachable-N, corn grain yield, N uptake, water and N use efficiency were compared between treatments. In HP-zones, corn grain yield and total biomass were 2.7 and 4.2 Mgha<sup>-1</sup> higher with SSM than UM, and corn grain N uptake and total N uptake increased by 21% and 18% with SSM when compared to UM. Soil residual-N at field-scale was reduced by 18% with SSM. Marginal differences in potentially leachable-N among treatments were observed throughout the soil profile; the highest nitrate concentration was 6.6 mg kg<sup>-1</sup> in LP-zones with UM within the 210–240 cm soil layer. Overall corn water use efficiency in total biomass was 16% higher with SSM than with UM in both LP- and HP-zones. Using SSM in the LP-zones increased corn N use efficiency in grain and total biomass by 50% and 43% respectively. In this context, SSM can be considered as a conservation practice that optimizes N and water use efficiency by corn under dry conditions.

**Publicado originalmente en:** Maria del Pilar Muschietti-Piana, Pablo Ariel Cipriotti, Susana Urricariet, Nahuel Raul Peralta, Mauricio Niborski. Using site-specific nitrogen management in rainfed corn to reduce the risk of nitrate leaching. *Agricultural Water Management*. 199: 61–70

DOI: <https://doi.org/10.1016/j.agwat.2017.12.002>